



Performance Filtration - 1440 S Hwy 121 Ste 4 Lewisville, TX 75067 (800) 866-2959 (f) 972-436-1932

Performance Filtration, Inc.
1440 Hwy 121 Ste 4
Lewisville, TX 75067
800-866-2959 or 972-434-2959
972-436-1932 (fax)

**"The Ultimate"
Synthetic Air Compressor Lubricant
Polyolester (POE) 46/68**

Product Information - MSDS Data Sheet

SYNTHETIC COMPRESSOR LUBRICANT

Polyolester lubricant is a high performance lubricant formulated specifically to outperform other synthetic rotary compressor lubricants on the market. **Polyolester** employs a unique base stock that allows improvements in oxidation resistance and sludge and deposit formation over conventional synthetic base stocks. It is also compatible with existing O.E.M. provided lubricants.

Physical Properties

Product Part- POE	46	68
PFI Part Number	4801	4932
ISO Grade	46	68
Viscosity:		
Cst @ 40°C	48.7	64.2
Cst @ 100°C	7.86	9.45
SUS @ 100°F	249	329
SUS @ 210°F	52.6	58.1
Viscosity Index	130	127
Specific Gravity	0.910	0.914
Flash Point °F (°C)	475 (246)	450 (232)
Pour Point °F (°C)	-55 (-48)	-50 (-46)
RBOT, Minutes	3038	3100

The information contained in this document is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability.